



SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product:	Pacer Silver Wheel Paint
Product Code:	PWP1
Product Use:	Application is by spray atomization from a handheld aerosol pack. Used for car touchups.
New Zealand Supplier:	Car Clean Products NZ Limited
Address:	33 Ha Crescent, Wiri Auckland
Telephone:	09 250 0091
Fax Number:	09 250 0092
Emergency Telephone:	0800 POISON (0800 764 766)
Date of MSDS Preparation:	October 2015

Section 2. Hazards Identification

Extremely flammable aerosol, harmful if swallowed or inhaled may cause skin or eye irritation.

Potential Health Effects



Swallowed	Not considered a normal route of entry. Do not induce vomiting. Give water to rinse out mouth, then provide liquid slowly.
Eyes	Immediately hold victims eyes open and flush with water for 15 minutes. Transport to hospital.
Skin	Flush skin and hair with running water and soap. Do not use solvents to remove.
Inhalation	Remove to fresh air. If symptoms persist seek medical attention.

Section 3. Composition / Information on Ingredients

Ingredients	Proportion (% mass)	CAS Number
Acetone	<60	67-64-1
Ingredients not contributing to classification	<10	
LPG	<60	68476-85-7

Section 4. First Aid Measures

Routes of Exposure:

Eye	Hold eyes open and flush with water for at least 15 minutes. Seek medical attentions immediately
Skin	Immediately remove contaminated clothing and wash skin and clothes thoroughly with soap and water. Apply soothing barrier cream if redness or irritation appears.
Ingestion	Do not induce vomiting. Rinse mouth with water. Seek medical attention immediately. Treat as for petrol ingestion.
Inhalation	Remove to fresh air. If breathing is difficult, seek medical attention immediately

Section 5. Fire Fighting Measures

Suitable Extinguishing media	Foam, Dry Chemical, Carbon dioxide
Fire and Explosion hazards	Flammable liquid and vapour. Vapour accumulation could flash and/or explode if ignited
Fire Fighting Instructions	Fire fighters must use recommended protective equipment and self-contained breathing apparatus. Hazchem 2Y

Section 6. Accidental Release Measures

Land Spill or Leaks	Evacuate spill area and eliminate all ignition sources. Report spill to fire brigade. If possible remove leaking containers to a detached area wearing approved respirator and personal protection equipment. Bund spill area with inert material. Avoid contact with skin and eyes. Do not breathe vapour. Extinguish naked flames. Remove ignition sources. No smoking. Evacuate the area of all
---------------------	--

non-essential personnel. Shut off leaks, if possible without personal risk. Wear full-face respirator with canister and filter

Section 7. Handling and Storage

Handling Advice: Store away from heat and open flames. Store at ambient temperatures. Keep containers tightly closed and in a well-ventilated place

Storing Procedures: Store away from heat and open flames. Store at ambient temperatures. Keep containers tightly closed and in a well-ventilated place. Do not store alongside food or feedstuffs.

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use only in well ventilated area. Eliminate sources of static buildup. Avoid physical damage to containers.

Personal Protective Equipment: General exhaust is adequate under normal conditions. If the risk of overexposure exists, wear SAA approved respirator.

Section 9 Physical and Chemical Properties

Physical State: Supplied as aerosol pack. Contents under pressure.

Colour: Silver

Odour: Sharp hydrocarbon smell

Solubility in water, % mass: Not soluble

Relative Vapour Density (air=1): >1

Boiling point: 56°C :

Ignition Point: Not available

Flash Point : -83°C (propellant)

Specific Gravity: 0.65-0.70

Vapour Pressure@ 20°C, Not available

Volatiles: 100%

Section 10. Stability and Reactivity

Chemical Stability Flammable. In use may form flammable/explosive vapour-air mixture

Conditions to Avoid Store away from heat and open flames. Store at ambient temperatures. Keep containers tightly closed and in a well-ventilated place.

Incompatibility Strong oxidizers. Flammable gases, explosives

Hazardous Decomposition
Products

Carbon dioxide in a fire

Section 11 Toxicological Information

Acute Oral Toxicity	Acute oral TDLo: 2857 mg/kg (Man)
Acute Dermal Toxicity	Acute dermal LD50 (rabbit) 20000 mg/kg.
Inhalation	Acute inhalation LC50 (rat) 50100 mg/kg 3/8 hr.
Long term Effects	Not available. Refer to individual constituents.

Section 12. Ecotoxicological Information

Environmental Precautions:

<i>Ecological Toxicity</i>	Not readily biodegradable and has potential to harm marine and terrestrial vertebrates and invertebrates
----------------------------	--

Environmental Fate:

<i>Soil</i>	Not readily biodegradable and has potential to bio accumulate
-------------	---

<i>Water</i>	Not readily biodegradable and has potential to bio accumulate
--------------	---

Environmental Exposure Limits	EEL _{water} Not set
-------------------------------	------------------------------

Section 13. Disposal Considerations

Dispose of waste at an appropriate waste disposal facility in accordance with local authority bylaws.

Empty and open containers can retain vapour residues for long periods of time risking unintended ignition or explosion.

Section 14 Transport Information

Road, Rail, Marine and Air Transport

UN No	: 1950
Class-primary	: 2.1
Packing Group	: II
Proper Shipping Name:	: Aerosols (Flammable)

Section 15	Regulatory Information
-------------------	-------------------------------

Primary HSNO Class	2.1
Subsidiary classes	6.1D, Skin irritant 6.3B, Eye irritant 6.4A Toxic to marine organisms 9.1D
Group Standard	Aerosols (flammable)

Section 16	Other Information
-------------------	--------------------------

Supplied in aerosol. Code: PWP1

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand proprietor, Car Clean Products NZ Limited,
Phone: 09 250 0091, if further information is required.



Car Clean Products NZ Limited
Ph + 64 9 250 0091 - Fax + 64 9 250 0092 - www.pacer.co.nz
33 Ha Crescent, Wiri - P O Box 97 948 - Manukau - Auckland 2241 - New Zealand

PACER AERO SILVER WHEEL PAINT

PURPOSE:

A lead free, fast drying enamel spray paint formulated for use on all metals, plastics and fiberglass. Ideal for reconditioning wheels, engine blocks, exhaust systems, radiators, motor mowers etc.

DIRECTIONS:

Clean surface thoroughly. Remove grease, oil, rust and loose paint with Pacer Prepare It. Mask surrounding area to protect from overspray.

Spray at room temperature. Shake can until agitator ball moves freely. Repeat during use.

Hold can upright 30-40cm from surface to be painted. Spray in short bursts, moving back and forth until evenly covered. Allow approximately 5 minutes between coats. Fully cured after 24 hours.

Turn can upside down after use and spray until clear to prevent valve from clogging.

WARNING:

FLAMMABLE – Do not store or use near heat, fire or flame.

Harmful if swallowed or inhaled. May cause skin and eye irritation.

USE IN WELL VENTILATED AREA